



**General
Information**



Installing a Danfoss GX Snow Melting System provides a permanent solution to the problems caused by cold weather. Improve safety by providing instantaneous relief from snow and ice and increase your bottom line by reducing the costs associated with applying chemicals, owning snow clearing machinery or hiring outside services.

- Twin conductor cable
- Single point connection
- Easy and flexible installation
- Durable construction
- Silent, efficient and safe
- For use in concrete, asphalt and under pavers
- Zero EMF's (Electromagnetic fields)
- Genuine ten year non-prorated warranty

Technical Data

Cable Construction:	Twin conductor
Rated Voltage:	208V, 240V, 277V, 480V, 600V
Output (Mats):	37W/sq.ft. (400W/m ²), 50W/sq.ft. (540W/m ²)
Output (Cables):	9W/ft. (35W/m), 12W/ft. (400W/m)
Cold Lead:	20 feet (6.0 m)
Bending Radius:	Minimum 1.5 inches (38 mm)
Cable Diameter:	1/4 inches (6.5 mm)
Conductor Insulation:	Teflon™ FEP
Filler Sheath:	PEX
Outer Insulation:	PVC
Max. Temperature:	220°F (105°C)
Min. Installation Temp:	40°F (5°C)

See power lead label for NEC connection color code.

**Ordering Information
GX Mats - 208V**

All mats are 2 feet wide.
Power leads are 20 feet in length.

Part No.	Length (feet)	Coverage (sq.ft.)	Watts (50W/sq.ft.)	Amps	Ohms
088L3222	6.5	15	640	3.1	67.0
088L3223	10.0	20	1,100	5.3	39.2
088L3224	12.5	25	1,280	6.2	33.5
088L3225	15.0	30	1,550	7.4	28.0
088L3226	17.5	35	1,730	8.3	25.0
088L3227	20.0	40	1,900	9.2	22.6
088L3228	22.5	45	2,100	10.1	20.6
088L3229	25.0	50	2,400	11.5	18.0
088L3230	30.0	60	3,050	14.7	14.1
088L3231	35.0	70	3,400	16.4	12.7
088L3232	40.0	80	3,800	18.3	11.4
088L3233	45.0	90	4,230	20.3	10.2
088L3234	50.0	100	5,000	24.1	8.6



Ordering Information GX Mats - 240V

All mats are 2 feet wide.
Power leads are 20 feet in length.

Watt Output of the 240V Mat is reduced by 25% when operated at 208V (approx. 37.5W/sq.ft.)

Part No.	Length (feet)	Coverage (sq.ft.)	Watts (50W/sq.ft.)	Amps	Ohms
088L3201	7.5	15	750	3.1	77.4
088L3202	10.0	20	1,000	4.2	57.1
088L3203	12.5	25	1,250	5.2	46.1
088L3204	15.0	30	1,500	6.3	38.1
088L3205	17.5	35	1,750	7.3	32.9
088L3206	20.0	40	2,000	8.3	28.9
088L3207	22.5	45	2,250	9.4	25.5
088L3208	25.0	50	2,500	10.4	23.0
088L3209	30.0	60	3,000	12.5	19.2
088L3210	35.0	70	3,500	14.6	16.4
088L3211	40.0	80	4,000	16.7	14.4
088L3212	45.0	90	4,500	18.8	12.8
088L3213	50.0	100	5,000	20.8	11.5
088L3214	57.5	115	5,750	24.0	10.0
088L3215	65.0	130	6,500	27.1	8.9

GX Mats - 240V (37W/sq.ft.)

All mats are 2 feet wide.
Power leads are 20 feet in length.

Part No.	Length (feet)	Coverage (sq.ft.)	Watts (37W/sq.ft.)	Amps	Ohms
088L3300	16.5	35	1,235	5.1	46.6
088L3301	20.0	40	1,480	6.2	38.9
088L3302	45.0	90	3,495	14.6	16.5
088L3303	60.0	120	4,505	18.8	12.8
088L3304	77.5	155	5,715	23.8	10.1

GX Mats - 277V

All mats are 2 feet wide.
Power leads are 20 feet in length.

Watt Output of the 277V Mat is reduced by 25% when operated at 240V (approx. 37.5W/sq.ft.)

Part No.	Length (feet)	Coverage (sq.ft.)	Watts (50W/sq.ft.)	Amps	Ohms
088L3255	30.0	60	2,800	10.1	27.4
088L3256	35.0	70	3,440	12.4	22.3
088L3257	40.0	80	4,080	14.7	18.8
088L3258	45.0	90	4,680	16.9	16.4
088L3259	52.5	105	5,100	18.4	15.1
088L3260	57.5	115	5,850	21.1	13.1



Ordering Information GX Mats - 480V

All mats are 2 feet wide.
Power leads are 20 feet in length.

Part No.	Length (feet)	Coverage (sq.ft.)	Watts (50W/sq.ft.)	Amps	Ohms
088L3270	10.0	20	1,000	2.1	228.6
088L3271	15.0	30	1,500	3.1	154.8
088L3272	20.0	40	2,000	4.2	114.3
088L3273	25.0	50	2,500	5.2	92.3
088L3274	30.0	60	3,000	6.3	76.2
088L3275	35.0	70	3,500	7.3	65.8
088L3276	40.0	80	4,000	8.3	57.8
088L3277	45.0	90	4,500	9.4	51.1
088L3278	50.0	100	5,000	10.4	46.2
088L3279	60.0	120	6,000	12.5	38.4
088L3280	70.0	140	7,000	14.6	32.9
088L3281	80.0	160	8,000	16.7	28.7

Ordering Information GX Mats - 600V

All mats are 2 feet wide.
Power leads are 20 feet in length.

Watt Output of the 600V Mat is reduced by 35% when operated at 480V (approx. 32.5W/sq.ft.)

Part No.	Length (feet)	Coverage (sq.ft.)	Watts (50W/sq.ft.)	Amps	Ohms
088L3290	12.5	25	1,250	2.1	288.0
088L3291	17.5	35	1,845	3.1	195.1
088L3292	25.0	50	2,485	4.1	144.9
088L3293	30.0	60	3,075	5.1	117.1
088L3294	37.5	75	3,715	6.2	96.9
088L3295	45.0	90	4,455	7.4	80.8
088L3296	50.0	100	5,050	8.4	71.3
088L3297	57.5	115	5,685	9.5	63.3
088L3298	62.5	125	6,280	10.5	57.3
088L3299	75.0	150	7,505	12.5	48.0



Controls

Part No.	Description	Voltage
088L3415	GX850M Dual Zone Controller*	120V, 240V
088L3411	GX850 ACP With Onboard 50A Contactor*	120V, 240V
088L3035	DS-2B Snow Melt Controller (30A)	120V, 240V
088L3035	DS-5 Snow Melt Controller (60A - 2x30A)	120V, 240V

*Requires ground and/or roof sensors

*Control voltage 120V

Timer/Contactor Panels

Part No.	Description	Max. Amps	Coil Voltage	No. of Contactors
088L3450	Single Contactor, 600V	40	120	1
088L3451	Single Contactor, 600V	40	208-240	1
088L3456	Single Contactor, 600V	60	120	1
088L3457	Single Contactor, 600V	60	208-240	1
088L3440	GX Timer Panel with 4hr timer, 600V	100	120	2
088L3441	GX Contactor Panel without timer, 600V	100	120	2
088L3442	GX Timer Panel with 4hr timer, 600V	200	120	4
088L3443	GX Contactor Panel without timer, 600V	200	120	4

All contactors are complete with NEMA 1 enclosure

100A contactor/timer panels consist of two, 3P, 50A contactors

200A contactor/timer panels consist of four, 3P, 50A contactors

Accessories

Part No.	Description
088L1050	Cable Strapping (15 ft.)
088L1054	Cable Strapping (75 ft.)
088L3051	Ground Sensors (two per package)
088L3053	Single Ground Sensor (one per package)
088L3052	Roof Sensor (includes 50 ft. lead wire)
088L3405	Nameplate (per NEC 426-13)
088L0010	GX Repair Kit (includes: crimp connectors, heat shrink tubes, repair wire)
088L3038	CDP-2 Remote Control and Display for Snow Sensors*
088L3039	CS-1 Remote Control/Monitor Pigtail for CDP-2
89999997	Extended Power Leads, factory spliced, 5 ft. increments**

*CDP-2 installation requires use of CS-1 pigtail

*CDP-2 can be used with DS-2B and DS-5 controllers

**Allow 6-8 weeks delivery time

Warranty

Genuine ten year comprehensive extended warranty against defects in material, design, and workmanship.

Technical Services

For technical questions, please contact Danfoss Heating Division North America at **1-866-676-8062**. More information on Danfoss Electric Heating products is available at **www.LX.Danfoss.com**.

Danfoss can accept no responsibility for possible errors in catalogs, brochures, other printed materials, and website information. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alteration can be made without subsequent changes being necessary in specifications already agreed upon. All trademarks in this material are property of the respective companies. Danfoss and Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Danfoss
Toronto
 Toll Free: 1-866-676-8062
 Tel.: 905-285-2050
 Fax: 905-285-2055
 www.LX.Danfoss.com

Danfoss GX
 BRINGING WARMTH TO LIFE